







PPP WELDING MACHINE



- · Double heating elements
- 1500 watt
- · Heat resistant cable; up to 300℃ is used
- X shape foot
- · On/Off switches have special illuminations to ensure easy working
- · Thermostat is provided
- · All apparatus required for PP welding are available in the toolbox set(20-40mm)
- · All products in the set comply with CE norms and guaranteed for 1 year

RS-1	Consist of machine, stand, Teflon coated die plates, iron box Scissor, glove, Balancing apparatus, 3 meter ruler, screwdriver, screw, Allen key							
Welding range	20m	20mm、25mm、32mm、40mm、50mm、63mm						
Power	1500 W	Voltage	e 22	220 V Fre		/	50 HZ	
Iron Box	Iron Box Size: 50*28*10 cm			Heat Plate Size: 16*7*2.1cm				
Temperature: 0-300°C				Usage: PPR PE PP				
Weight	Total Ma		Machine	hine Iron box		Heat plate		
weight	5.5kg		2.1 kg	2.8 kg		550g		
Day Cartan	Quantity / CTN		Weig	Weight / CTN		Size / CTN		
Per Carton	5		2	28kg		51*30*53 cm		
Die Head	20mm 20mm		25mm	25mm	32n	nm	40mm	
Weight	70g	70g	93g	93g	14:	2g	200g	



- · Double heating elements
- · Heating element made of noncorrosive material
- 2000 watt
- Heat resistant cable; up to 300°C is used
 Special foot with clamp that enables working on any location are available
- On/Off switches have special illuminations to ensure easy working
- · Thermostat is provided
- · All apparatus required for PP welding are available in the toolbox set(20-63mm)
- · All products in the set comply with CE norms and guaranteed for 1 year

RS-2	Consist of machine, stand, Teflon coated die plates, iron box,screw, Allen key Heat plate, scissor, glove, Balancing apparatus, 3 meter ruler, screwdriver,							
Welding range	20n	20mm、25mm、32mm、40mm、50mm、63mm						
Power	2000 W	Voltag	je 22	220 V Fre		50 HZ		
Iron Box		Heat Plate Size: 19*8.8*1.78 cm						
Temperature: 0-300°C				Usage: PPR PE PP				
Total		N	Machine		ох	Heat plate		
Weight	6.05 kg		1.87 kg	2.6 kg	1	650g		
Day Cartan	Quantity / CTN		Weigh	Weight / CTN		Size / CTN		
Per Carton	5		30	30.5 kg		0*53 cm		
Die Head	20mm	25mm	32mm	40mm	50mm	63mm		
Weight	55.3 g	75 g	109.7 g	144.3 g	200.2 g	333.2 g		





- Digital display
- 1000 watt
- Heat resistant cable; up to 300°C is used
- Thermostat is provided
- All apparatus required for PP welding are available in the toolbox set(20-32mm)
- All products in the set comply with CE norms and guaranteed for 1 year

RS-3	Consist of machine, stand, Teflon coated die plates, iron box Screwdriver, screw,Allen key						
Welding range		20mm、25mm、32mm					
Power	1000 W	Voltage	22	20 V Frequenc		50 HZ	
Iron Box S	Heat Plate Size: 13*6.2*1.78 cm						
Temperature: 0-300°C			Usage: PPR PE PP				
Weight	Total	N	lachine	chine Iron b		Heat plate	
weight	3.55 kg	C).98 kg	g 1.8 kg		370g	
Per Carton	Quantity / CTN		Weigh	Weight / CTN		Size / CTN	
Per Carton	3		11 kg		40*22*25.5cm		
Die Head	Die Head 20mm		25mm		32mm		
Weight	83 g		101.7 g		161.8 g		



- · Digital display
- 1000 watt
- · Heat resistant cable; up to 300℃ is used
- · Thermostat is provided
- All apparatus required for PP welding are available in the toolbox set(20-63mm)
- · All products in the set comply with CE norms and guaranteed for 1 year

RS-4	Consist of machine, stand, Teflon coated die plates, iron box, Screwdriver, screw, Allen key								
Welding range	20n	20mm、25mm、32mm、40mm、50mm、63mm							
Power	1000 W Voltage			220	0 V Frequency		equency	50 HZ	
Iron Box Size: 42*25*10.5 cm				Heat Plate Size: 14.5*7.5*1.78 cm					
Temperature: 0-300°C				Usage: PPR PE PP					
Weight			Mach	achine Iron box				Heat plate	
weight	5.7 kg	1.2		kg	2.45 kg			510g	
D C t	Quantity / CTN			Weight / CTN		Size / CTN			
Per Carton	3			17.5 kg			43*26*33 cm		
Die Head	20mm	25mm		32mm	40mm	1	50mm	63mm	
Weight	83 g	101.7 g		161.8 g	242 g	1	420.8 g	622 g	



- Digital display
- · 1200 watt
- · Heat resistant cable; up to 300℃ is used
- · Possible to work with welding socket up to 110mm
- Thermostat is provided
- All apparatus required for PP welding are available in the toolbox set(75-110mm)
- All products in the set comply with CE norms and guaranteed for 1 year

RS-5	Consist of machine, stand, Teflon coated die plates, iron box Screwdriver, screw, Allen key							
Welding range	75mm、90mm、110mm							
Power	1200 W	Voltage		220	V	Frequency	y 50 HZ	
Iron Box Size: 45*31.5*10.5 cm				H	leat Plate Siz	e: 13.2*14	.5*1.78 cm	
Temperature: 0-300°C				Usage: PPR PE PP				
Weight	Total	Mach		nine	Iron l	оох	Heat plate	
weight	7.4 kg		1.53 kg		3.15	kg	750g	
D Ct	Quantity /	ntity / CTN		Weight / CTN			Size / CTN	
Per Carton	3			23 kg		46*31.5*33cm		
Die Head	Die Head 75mm		90mm			110mm		
Weight	497 g		691 g			1081 g		

SMPLAST





WELDING

RS-6

- · Common manual temperature controlling
- 600 watt
- · Heat resistant cable; up to 300°C is used
- · Thermostat is provided
- All apparatus required for PP welding are available in the toolbox set(20-32mm)
- All products in the set comply with DIN norms and guaranteed for 1 year





WELDING

RS-7

- Common manual temperature controlling
- · 800 watt
- · Heat resistant cable; up to 300°C is used
- · Thermostat is provided
- All apparatus required for PP welding are available in the toolbox set(20-63mm)
- All products in the set comply with DIN norms and guaranteed for 1 year



WELDING

RS-8

- Common manual temperature controlling
- 600 watt
- Heat resistant cable; up to 300℃ is used
- Thermostat is provided
- All apparatus required for PP welding are available in the toolbox set(20-32mm)
- All products in the set comply with DIN norms and guaranteed for 1 year





WELDING

RS-9

- Common manual temperature controlling
- · 800 watt
- · Heat resistant cable; up to 300°C is used
- · Thermostat is provided
- All apparatus required for PP welding are available in the toolbox set(20-63mm)
- All products in the set comply with DIN norms and guaranteed for 1 year









TM-C-01

TM-C-02

TM-C-03

FEATURES:

- Apply for pvc, aluminum or plastic pipes, gas pipe, electrical appliance pipe and other plastics pipeline. (not to be applied on electric cableline and steel pipe)
- Cutting pvc flexible pipe, revolve it whilst pressing the handles.

MAX.WORKING SIZE:

TM-C-01	TM-C-02	TM-C-03
42mm	42mm	63mm

TM-C-4



Maxim Pressure	60 bar
Container	12Liter
Connection	R1/2"
Measurement	510/180/290mm
Swept Volume	ca.45 ml